## ORDINANCE EXHIBIT "A"



## LEGAL DESCRIPTION For: Toledo Lucas County Port Authority

Front Street Right of Way Easement to be Released 1.522 Arres

Part of Lots 10-13 Block H, Lots 8-11 Lots 10-13 Block G, Lots 10 and 11 Block K of the Plat of Ellenboro, part of Lots 13-16 of the Plat of Niles Addition, and part of Lots 3 and 4 of Fractional Section 28, Town 9 South, Range 8 East, City of Toledo, Lucas County, Ohio and being further bounded and described as follows:

Commencing from a 1-inch iron pin in a monument box found marking the intersection of the centerline of Front Street (right of way varies) with the centerline of Millard Avenue (right of way varies);

Thence Southwesterly along the centerline of said Front Street, South 43 degrees 18 minutes 33 seconds West, a distance of 40.02 feet to a 3/4-inch Iron pin in a monument box found marking a point of intersection;

Thence Northwesterly along the centerline of said Front Street, North 46 degrees 26 minutes 59 seconds West, a distance of 10.09 feet to a point of intersection;

Thence Southwesterly along the centerline of sald Front Street, South 43 degrees 21 minutes 49 seconds. West, a distance of 178.99 feet to a 3/4-inch iron pin in a monument box found marking a point of intersection;

Thence Southwesterly along the centerline of sald Front Street, South 35 degrees 39 minutes 17 seconds. West, a distance of 652.01 feet to a point;

Thence Southeasterly along a line perpendicular to the centerline of said Front Street, South 54 degrees 20 minutes 43 seconds East, a distance of 30.00 feet to a mag nall found marking the intersection of the Easterly right of way line of said Front Street with the Northerly right of way line of Randolph Street (60' right of way);

Thence continuing Southeasterly along the Northerly right of way line of said Randolph Street, South 54 degrees 20 minutes 43 seconds East, a distance of 35.05 feet to a point;

Thence Southwesterly along a line, South 30 degrees 37 minutes 00 seconds West, a distance of 60.23 feet to the True Point of Beginning of the parcel herein described;

- Thence continuing Southeasterly along the Southerly right of way line of said Randolph Street, South 54 degrees 20 minutes 43 seconds East, a distance of 79.66 feet to a point;
- Thence Southwesterly along a line, South 35 degrees 39 minutes 17 seconds West, a distance of 624.25 feet to a point;
- Thence Southwesterly along a line, South 30 degrees 39 minutes 17 seconds West, a distance of 346.81 feet to a 5/8-inch iron pin found;
- Thence Southeasterly along a line, South 54 degrees 20 minutes 43 seconds East, a distance of 49.65 feet to a point;
- Thence Southwesterly along a line, South 35 degrees 39 minutes 43 seconds West, a distance of 55.54 feet to a point;
- Thence Northwesterly along a line, North 54 degrees 20 minutes 17 seconds West, a distance of 35.86 feet to a point;
- Thence Southwesterly along a line, South 80 degrees 39 minutes 43 seconds West, a distance of 110.55 feet to a point;
- Thence Northeasterly along a line, North 34 degrees 52 minutes 07 seconds East, a distance of 87.41 to a point;
- Thence Northeasterly along a line, North 39 degrees 28 minutes 21 seconds Fast, a distance of 96.89 feet to a point;
- Thence Northeasterly along a line, North 33 degrees 57 minutes 05 seconds East, a distance of 188.93 feet to a point;
- Thence Northeasterly along a line, North 32 degrees 24 minutes 32 seconds East, a distance of 182.31 feet to a point;
- Thence Northeasterly along a line, North 32 degrees 34 minutes 33 seconds Fast, a distance of 200.39 feet to a point;

Front Street Right of Way Easement to be Released 1.522 Acres

- 13: Thence Northeasterly along a line, North 34 degrees 28 minutes 46 seconds East, a distance of 196.60 feet to a point;
- 14. Thence Northeasterly along a line, North 30 degrees 37 minutes 00 seconds East, a distance of 152.74 feet to the True Point of Beginning, containing in all 1.522 acres of land more or less, subject however to all legal highways and prior easements of record.

The above legal description is based on a land survey performed during August of 2017, by DGL Consulting Engineers, LLC. and was prepared by Ronald J. Lumbrezer, Ohio Professional Surveyor #8029.

<u>NOTE:</u> The bearings in this legal description are based upon an assumed meridian and are used only for the purpose of describing angular measurements.

All reférences to "an iron pin set" are 5/8" diameter x 30" long iron pins with cap "DGL – FUL 8029"

Ronald J. Lumbrezer, P.S.

Ohio Professional Surveyor #8029

DGL Consulting Engineers, LLC 3455 Briarfield Blvd, Sulte F

Maumee, Ohlo 43537

Phone: (419)535-1015, Ext 232

1-5-19

RONALD J. LUMBREZER 8029

DGL COMSULTING ENGINEERS, LLC www.dgl-ltd.com

Page | 3

17% Legal Description 7/23/2018 Approved As C

